

ARCA 507030W

FIBOX
Enclosing innovations



Sample image

Order symbol : ARCA 507030W

Product nr : 8120151

UL Code : UL508A

Description : Cabinet, PC


Remarks : Grey cover with window, 2-point locking, hinges on the short side

EAN : 6418074086068

El. number :

- Finland : 3424070
- Denmark : 8212095465
- Sweden : 2500153

Including : Cabinet base. door with PUR gasket. mounting plate. screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.



Dimensions :	Height	Width	Depth
mm :	500	700	300
inch :	27.56	19.69	12.2

Materials :

Material :	Polycarbonate
Base colour :	RAL_7035

Accessories :

SBK ARCA 50	Support bar kit (435 x 40 x 30)
MPX ARCA 7050	Mounting plate (630x430 mm)
PMK ARCA 70	PoleMounting kit, for pole ø100-300mm (685 x 485 x 35)
RCS ARCA 5070	Rain canopy set for size 5070

Cover colour : Clear transparent

Gasket material : Polyurethane

Temperatures :

Temperature °C (short term) : -40 ... 120

Temperature °C (continuous) : -40 ... 80

Temperature °F (short term) : -40 ... 250

Temperature °F (continuous) : -40 ... 175

DSP ARCA RM Door stopper ARCA, right, midsize 5070-8060

DRS ARCA 507030 DIN rail frame set (685 x 485 x 35)

IDS ARCA 5070 Inner door set

SBK ARCA 70 Support bar kit (615 x 50 x 30)

DSP ARCA LM Door stopper ARCA, left, midsize 5070-8060

MPS ARCA 7050 Mounting plate (630x430x2 mm) (630 x 430 x 2)

MPMP ARCA 7050 Mounting plate multiperforated (630x430x2 mm - ø3.6 mm)

MPP ARCA 5070 Mounting plate perforated (630x430x2 mm - 26x11 mm)

Ratings :

Ingress protection (EN 60529): IP65;

Impact Resistance (EN 62262): IK08;

electrical_insulation : Totally insulated

Halogen free (DIN/VDE 0472, Part 815) : Yes

UV resistance : UL 508

Flammability Rating : UL 94 5VA

Glow Wire Test (IEC 695-2-1) °C : 960C

Certificates :

Certificate FI 40467